

ARGILE

couleurs de terre

ARGILE blanc plafond

Classification : Afnor NFT 36005 – Family I class 2b/4a

CHARACTERISTICS

Description	"ARGILE blanc plafond" is water based acrylic matt paint without tension avoiding any visible overlapping and drying marks, formulated with limed oils, partly renewable and natural.
Destination	All standard interior surfaces untreated or already painted (walls, ceilings, on top of old paint coats, woodwork...). This product is very much adapted for ceilings, knowing its very white and mat aspect, smooth effect, and also its easiness at applying and its isolating and masking power.
Qualities	Without tension (does not stress the substrate) Very good opacity Recoatible fresh into fresh Blocks and isolate marks and spots (nicotine, dirtiness, greasy marks, fire black marks...)
VOC	Limit value for this product (cat A/a : 30 g/l). This product contains max 10g/L of VOC
Emissions in indoor air Label	A+ class according ISO 16000 norm. European Ecolabel
Appearance	Deep smooth mat.
Application / painting	Brush Paint / spray gun Roller (6-8mm).
Density	1.53+/- 0,05 Kg/l
Coverage	Between 10 and 13 m ² / l. depending on surface.
Drying time at 20°C	Touch dry after 2 hours, re-coat after 8 hours maximum. Recoatible fresh into fresh, or after 12 hours if many marks.
Washability	Washable with a damp sponge. Do not use detergent to wash. Avoid mechanical actions, hard wiping, rubbing with a rag etc.)

INSTRUCTION FOR USE

Conditions necessary to paint	Air and surface temperature between 10°C and 25°C
Relative humidity	Maximum 60%
Thinners / dilution	Ready to use – Dilute with water on particularly absorbent surfaces or if applying with spray gun (5-10%)
To clean tools	Water
Colours	White and pastel
Availability	5L - 10L

INSTRUCTION FOR USE

Destination	<p>This deep matt product is very much adapted for ceilings, knowing its very white and mat aspect, smooth effect, and also its easiness at applying and its isolating and masking power.</p>
Preparation of surfaces	<p>The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France). Surfaces should be dry, the room well-ventilated, and air temperature between 10 and 25°C.</p> <p>"ARGILE blanc plafond" is designed to be used on all types of interior surfaces (walls, ceilings, woodwork) after the pre-application procedures have been carried out (cleaning, sand-papering...)</p> <p>On plaster, plaster recoated by a sheet of carton, water based filler, apply a first coat of "ARGILE blanc plafond" or "ARGILE sous couche de préparation".</p> <p>If covering a matt or absorbent paint notably on ceilings, apply an undercoat of "ARGILE blanc plafond" or "ARGILE sous couche de préparation".</p> <p>On shiny and smooth paint, after sand-papering apply an undercoat of "ARGILE primaire universel"</p> <p>On old wall covering or old sticky coatings, then sand-down regularly if you notice any straitening of fibers and apply directly two coatings of "ARGILE blanc plafond".</p>
Application	<p>Mix well manually before using the product.</p> <p>Apply two coats of "ARGILE mat profond" with brush, spray gun or roller (12mm polyamide or microfibre).</p> <p>In case of applying the paint with a spray gun, dilute it by 10% of water.</p>

Maintenance
Health and Safety

Using a brush will obtain a decorative brushed effect.
With the roller, the effect will be finely structured.

"ARGILE blanc plafond" can be cleaned gently with a warm sponge. Do not scrub or use detergent.

Keep out of reach of children.
Use only in well ventilated areas

In accordance with the development of our knowledge and of our techniques, this information sheet may be modified over the course of time.

ARGILE SAS - PA les Bellevues 35/37 av. du gros Chêne
Herblay - BP 90076 Eragny-sur-Oise
95611 Cergy-Pontoise Cedex
33 (0)1 34 44 11 00 - contact@argile-peinture.com
www.argile-peinture.com

SAS au capital de 399 500 euros
RCS Pontoise B 482 157 484
SIRET 482 157 484 00031
TVA FR25482157484