

# ARGILE

couleurs de terre

## **ARGILE MAT PROFOND**

Description: "ARGILE mat profond" is water based acrylic matt paint. Odourless, decorative and easy to apply, it is suitable for all types of interior work

Destination: all standard interior surfaces untreated or already painted (walls, ceilings, on top of old paint coats, woodwork...)

Qualities:

- odourless
- clean tools with water
- good coverage
- easy to apply
- quick to dry (re-coat after only 6 hours)

VOC: Limit value for this product (cat A/a : 30 g/l). This product contains max 1g/L of VOC.

## **Characteristics**

Appearance: Deep mat (3% shine)-Powdery appearance

Destination: interior – for use in normal rooms. Avoid using in damp rooms or areas that are subject to frequent rubbing (children's bedrooms, bathrooms, stairwells...)

Application / Painting: brush  
spray gun  
textured 12mm polyamide roller

Density: 1.42

Coverage: 10 m<sup>2</sup> per liter

Drying time at 20°C: touch dry after 2 hours, re-coat after 6 hours

Washability: washable with a damp sponge. Do not use detergent to wash. Avoid mechanical actions, hard wiping, rubbing with a rag etc.)

Conditions necessary to paint: -air and surface temperature between 10°C and 25°C  
-relative humidity: maximum 60%

Thinners / Dilution: ready to use – dilute with water on particularly absorbent surfaces or if applying with spray gun (10-20%)

To clean tools: water

Colours: 128 colours

Availability: 0.75, 2.5, 5 and 10 liters cans

## **Instructions for use**

### Destination:

This very matt, very fine textured decorative product is designed for use in normal rooms (bedrooms, living rooms, offices, corridors etc...)

It is therefore recommended that you do not use this product in areas that are frequently subjected to rubbing and washing (stairwells, children's bedrooms, also avoid damp and humid conditions). In such circumstances we recommend using "ARGILE laque satinée intérieure", since the outer coat is much more durable, washable and scrubbable

### Preparation of surfaces:

The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France). Surfaces should be dry, the room well-ventilated, and air temperature between 10 and 25°C.

"ARGILE mat profond" is designed to be used on all types of interior surfaces (walls, ceilings, woodwork) after the pre-application procedures have been carried out (cleaning, sand-papering...)

- on plaster, *plaster* recoated by a sheet of carton, water based filler, apply a first coat of "ARGILE sous couche de préparation"
- on particularly absorbent, dusty or chalky surfaces, or having filled in the plaster, apply a solvent based primer.
- on already painted surfaces, check the adherence of the previous coat; remove the parts that are not adhesive, then wash and sand-paper the area. Also carry out any filling in and repairing that are necessary
- on shiny and smooth paint, after sand-papering apply an undercoat of "ARGILE primaire universel"
- if covering a matt or absorbent paint notably on ceilings, apply an undercoat of "ARGILE sous couche de préparation"
- on non-ferrous metals and other surfaces with poor sticking qualities (hard plastic, PVC...), after sanding-papering apply a coat of "ARGILE primaire universel"
- on ferrous metals, use an appropriate anti rust primer (consult us)
- on untreated wood, after degreasing and sand-papering apply a coat of undiluted "ARGILE primaire universel"
- when degreasing wood, use an appropriate liquid degreaser (trichloroethylene, acetone...)
- on coated wood (varnish, paint, paint), remove any non-adhesive parts, and after sand-papering apply an undercoat of "ARGILE primaire universel"
- with derivatives of wood (melamine, laminated...), after sand-papering apply an undercoat of "ARGILE primaire universel"

- with furniture, remove all traces of polish, sand-paper thoroughly or scour off any old varnish. Then apply a coat of "ARGILE primaire universel", followed by two coats of "ARGILE mat profond". Protect any particularly exposed surfaces (to rubbing, bumps, or liquid etc...) with one or two coats of an appropriate varnish (consult us)
- on *old wall covering* or old sticky coatings, apply a coating of "ARGILE primaire universel", then sand-down regularly if you notice any straitening of fibers.
- if any old coatings have been stripped off, be sure to remove any traces of glue with the appropriate products

### **Application**

Mix well manually before using the product

Apply two coats of "ARGILE mat profond" with brush, spray gun or roller

Use a textured polyamide 12mm roller

In case of applying the paint with a spray gun, dilute it by 20% of water

Using a brush will obtain a decorative brushed effect

With the roller, the effect will be finely structured

### **Maintenance**

"ARGILE mat profond" can be cleaned gently with a warm sponge. Do not scrub or use detergent

### **Health and Safety**

Keep out of reach of children. Use only in well ventilated areas

In accordance with the development of our knowledge and of our techniques, this information sheet may be modified over the course of time.