

# ARGILE

couleurs de terre

## **ARGILE MAT VELOUTE**

Description: "ARGILE mat velouté" is acrylic and polyuréthane water based paint, with a smooth, taut and silky appearance .

Destination: all interior surfaces: walls, ceilings, doors, mouldings, old paint, wood, etc...

Qualities:

- odourless
- clean all tools in water
- good coverage
- easy to use
- quick to dry (you can recoat after 6 hours)

VOC : -Limit value for this product (cat A/a) : 30 g/litre (2010). This product contains max 30 g/L of VOC

## **Characteristics**

Appearance: smooth/velvety (10% shine at 85°)

Destination: interior

Application / Painting: brush  
paint / spray gun  
roller (insulated foam roller or textured 6-8mm polyamide)

Density: 1.45

Coverage: up to 10 m<sup>2</sup> per liter depending on surface

Drying time at 20°C: touch dry after 2 hours, re-coat after 6- 12 hours maximum

Conditions necessary to paint: -air and surface temperature between 10°C and 25°C  
-relative humidity: maximum 60%

Thinners / Dilution: ready to use, dilute with water by 5-10% on particularly absorbent surfaces or if applying with spray gun

To clean tools: water

Colours: 128 colours

Availability: 0.75, 2.5, 5 and 10 liters cans

Washability: washable with a warm sponge. Do not scrub or use detergent. Avoid using mechanical actions, hard wiping, rubbing with a rug ...)

## **Instructions for use**

### Destination:

This decorative product, with a very subtle velvety appearance and a remarkably fine texture, is meant for any normal rooms (bedrooms, living rooms, offices, corridors etc...)

It should therefore not be used on surfaces that are subject to frequent washing or particularly hard use (areas that are constantly rubbed, children's bedrooms, stairwells, or areas of high humidity...)

In such circumstances we recommend using "ARGILE laque satinée intérieure", since the outer coat is much more durable, washable and scrubbable

### Preparation of surfaces:

The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France). Surfaces should be dry, the room well-ventilated, and air temperature between 10 and 25°C.

"ARGILE mat velouté" is to be applied, after following the pre-use instructions (cleaning, degreasing, sand-papering...), to the following interior surfaces:

-plaster, plaster covered by a sheet of carton, water based filler, apply a first coat of "ARGILE sous couche de préparation"

-on particularly absorbent, dusty or chalky surfaces, or on repaired or filled surfaces, apply a solvent based primer.

-on already painted surfaces, check the adherence of the previous coat, remove the parts that are not adhesive, wash and sand-paper the area. Also carry out any filling in that are necessary

-on old matt paint, especially in the case of ceilings, apply a first coat of "ARGILE sous couche de préparation"

-on shiny or silky surfaces, clean and then sand-paper thoroughly, apply one coat of "Argile primaire universel"

-with non-ferrous metals, or if the surface or the adherence is poor (PVC, hard plastic...), clean and then sand-paper, apply first one coat of "Argile primaire universel"

-with untreated wood, degrease, clean, sand-paper, and then apply a first coat of "Argile primaire universel"

-the degreasing of wood should be done with specific degreasing liquid (trichloroethylene, acetone...)

-with covered wood (with paint, stains, or varnish...) remove the non-adhesive parts and sand-paper them, apply one coat of "Argile primaire universel"

-on derivatives of wood (melamine, laminated wood...), clean and sand-paper, apply one coat of "Argile primaire universel"

-for furniture, remove all traces of polish or wax, sand-paper it thoroughly and scour off any old varnish. Then apply a coat of "ARGILE primaire universel", followed by two coats of "ARGILE mat velouté".

-on old wall paper or wall covering , apply a coating of "ARGILE primaire universel", then sand-down regularly if you notice any straightening *of the fibers*.

-if any old wall covering have been stripped off, be sure to remove any traces of glue with the appropriate products

### **Application**

Stir well manually before using the product

Apply two coats of "ARGILE mat velouté" with brush, spray gun or roller.

On smooth surfaces, those are perfectly prepared use a polyamide textured 6mm roller. On other surfaces, use a polyamide textured 6-8mm textured roller.

Using a brush will obtain a taut appearance.

When using a spray gun, dilute the product with water by 5-10%.

### **Upkeep/Maintenance**

"ARGILE mat velouté" can be cleaned with a warm sponge. Avoid aggressive scrubbing. Use soft detergents if necessary.

### **Health and Safety**

Keep out of reach of children. Use only in well ventilated areas.

In accordance with the development of our knowledge and of our techniques, this information sheet may be modified over the course of time.