

ARGILE PRIMAIRE UNIVERSEL

Description : « ARGILE Primaire universel » is an acrylic paint , water based , used as a primer, a primary paint, to give a very good adherence on hard and difficult substrates, before to apply the Argile range paints.

Destination : all interior surfaces , hard and difficult to paint, like PVC, plastic , hard wood, hard varnishes, hard glossy paints, non ferrous metal etc...

Advantages : - without smell
- garnishing,
- very good opacity
- very good adherence
- tools can be cleaned with water
- easy to apply
- quick to dry
- tense , very flat and nice aspect, before to be painted

COV : - Limit value for this product (cat A/i : 140 g/l). This product contains max 70 g/L of VOC.

Air Emission : low solvent waste (class A+ according ISO 16000 norm).

CHARACTERISTICS

Aspect : Satin, tense, flat and regular aspect.

Destination : Inside use, hard substrates

Application : Brush
Spray gun
Roller (Textured 7 mm polyamide roller by example)

Coverage : 10- 12 m² per liter, according to substrate

Drying time at 20°C : touch dry after 2 hours, recoatable after 6 hours.

Necessary conditions for painting: -air and surface temperature between 10°C and 25°C
-relative humidity: maximum 60%

Thinners / Dilution: ready to use

Cleaning tools : water

Colours: white, can be tinted with appropriated colorants.

Availability: 0.75, 2.5, and 5 liters cans

INSTRUCTION FOR USE

Destination :

Hard and difficult substrates (PVC, plastic, wood, non ferrous metal, ancien paint and varnishes, furnitures, doors etc..)

Preparation of surfaces:

The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France). Surfaces should be dry, the room well-ventilated, and air temperature between 10 and 25°C.

- on old and hard paints and varnishes, clean, sand, remove non adherant parts , apply one coat of "Argile primaire universel"
- on all hard surfaces, clean, sand, apply one coat of "Argile primaire universel"

Application

Mix well manually before using the product

Apply two coats of "ARGILE satin couvrant" with brush, spray gun or roller

Use a textured polyamide roller, 7mm by example

In case of applying the paint with a spray gun, dilute it by 5-10% of water

Health and Safety

Keep out of reach of children. Use only in well ventilated areas

Consult our technical data sheet

In accordance with the development of our knowledge and of our techniques, this information sheet may be modified over the course of time.